



ALRITE STANDARD GYPSUM BOARD

PRODUCT DATA SHEET



Alrite Standard Gypsum Board is designed to meet all drylining requirements. Manufactured from high-quality, environmentally friendly gypsum and finished with premium paper liners on both sides, it offers excellent strength, flexibility, and durability for a long service life.

AREAS OF APPLICATION

Designed for use as a lining board in wall and ceiling systems where fire and acoustic requirements are minimal. Not recommended for use in high-humidity areas.

COMPLIANT STANDARDS

- GB9775-2025;EN520 Type A
- AS/NZS 2588:2018

PRODUCT BENEFITS

- Durable and adaptable
- Available in tapered or square edge profiles
- Recyclable material
- Simple and efficient installation
- Can be layered for enhanced performance
- Delivers a smooth, ready-to-finish surface
- Features EPD-certified face and back paper for enhanced sustainability credentials

PERFORMANCE DATA

Thickness (mm)	Reaction to Fire (R2F)	Thermal Conductivity (W/mK)	Water Vapour Resistance (μ) (Dry/Wet) (EN12524)	Weight Per Square Meter (kg/m ²)
10	A2-s1, d0	0.25	10/4	7.5
13	A2-s1, d0	0.25	10/4	9.2

ALRITE STANDARD GYPSUM BOARD